Amendments to the Claims

This listing of claim will replace all prior versions and listings of claim in the application.

1.   (currently amended) A method for obtaining streaming content from a processing device network, comprising:

requesting an interface program from a first processing device in the processing device network;

downloading the interface program to a second processing device in the processing device network;

displaying a user interface on a display of the second processing device;

requesting by the interface program a streaming media file from a third processing device on the processing device network;

downloading the streaming media file to the second processing device, wherein the streaming media file includes an embedded code;

detecting an embedded code that includes information that represents an address to a remote common gateway interface;

spawning a the remote common gateway interface process that retrieves objects from a data store by the interface program in response to the information that represents an address responsive to the embedded code;

parsing the embedded code into a plurality of code segments by the process;

querying a memory location in a data the data store responsive to a code segment in the plurality of code segments; and,

responding to rules in the memory location.

2.   (currently amended) The method of claim 1, wherein the rules include updating the displayed user interface with a high resolution image stored in the data store and providing video responsive to the streaming media file.

3.   (previously presented) The method of claim 1, wherein the first processing device and the second processing device are different process devices.

4.   (original) The method of claim 1, wherein the second processing device is a personal computer having a web browser.

5.   (original) The method of claim 1, wherein the second processing device is a box coupled to a television.

6.   (currently amended) The method of claim 1, wherein the <u>streaming</u> media file is a advanced streaming format (.ASF) file.

7.   (currently amended) The method of claim 1, wherein the <u>streaming</u> media file is a real network media (. RM) file.

8.   (original) The method of claim 1, wherein the displayed user interface includes a first window, a second window, and a third window, wherein video is provided in the first window, a high resolution image is provided in the second window and text is provided in the third window.

9.   (original) A method of claim 1, wherein the third processing device is a media server.

10.   (currently amended) The method of claim 1, wherein the downloading step includes buffering a portion of the <u>streaming</u> media file.

11.   (previously presented) The method of claim 1, wherein the embedded code is a metadata time code having a format of a process identification, a variable and a target destination.

12.   (cancelled)

13.   (original) The method of claim 1, wherein the embedded code is a metadata time code.

14.   (currently amended) The method of claim 1, wherein the responding step (j) includes updating the user interface display.

15.   (currently amended) A system, comprising:
        a first processing device having a web browser;
        a data store ~~capable of storing~~ <u>to store</u> information; and,

a second processing device coupled to the first processing device and the data store, ~~capable of providing~~ to provide the first processing device with (1) a displayed user interface and (2) a <u>streaming</u> media file having an embedded code <u>including an address to a remote common gateway interface process</u>; wherein the user interface detects the <u>address</u> ~~embedded code~~ during a <u>streaming</u> media file download to the first processing device and, wherein the second processing device creates ~~a process for retrieving the information from the data store~~ <u>the remote common gateway interface process that retrieves objects, including the information, from the data store, in response to the address</u> ~~responsive to the embedded code~~, which is used to alter the displayed user interface while the <u>streaming</u> media file is used to display a video.

16.   (previously presented)   The system of claim 15, wherein the first and second processing devices are computers.

17.   (cancelled)

18.   (original) The system of claim 15, wherein the data store is a disk drive.

19.   (original) The system of claim 15, wherein the embedded code is a metadata time code.

20.   (previously presented) The system of claim 15, wherein the first processing device and the second processing device is coupled to the Internet.

21.   (original) The system of claim 15, wherein the first processing device and the second processing device is coupled to an intranet.

22.   (currently amended)   An article of manufacture, including a computer readable memory, comprising:

    a first software component ~~capable~~ to provide <u>a</u> streaming media <u>file</u> to a client;

    a second software component ~~capable~~ to detect an embedded code <u>having an address</u> in the streaming media <u>file</u>; and

    a ~~third software component capable to access a data store~~ <u>remote common gateway interface process that retrieves objects from a data store</u> ~~responsive to the embedded code~~ <u>in response</u>

- 4 -

to detecting the address in order to update a user interface while providing <u>video responsive to</u> the streaming media <u>file</u>.

23. (original) The article of manufacture of claim 22, wherein the data store includes a software object having rules, and where the rules are used to update a user interface.

24. (currently amended) A method for providing content, comprising:

downloading a streaming media <u>file</u> ~~content~~ having an embedded code <u>including a process identification to a remote common gateway interface process</u>;

detecting the ~~embedded code~~ <u>the process identification</u>;

passing a segment of the embedded code to <u>the</u> ~~a process~~ <u>remote common gateway interface process that retrieves objects from a data store</u>;

accessing ~~a database~~ <u>the data store</u> using the segment of the embedded code; and

downloading information, stored in the ~~database~~ <u>data store</u>, to provide content to a user interface while displaying <u>video in response to</u> the streaming media ~~content~~ <u>file</u>.

25. (currently amended) The method of claim 24, wherein the embedded code includes a format having ~~a~~ <u>the</u> process identification, a variable and a target destination.

26. (currently amended) A method, comprising:

downloading a streaming media ~~content~~ <u>file</u> having an embedded code including ~~a field~~ <u>information</u> representing an address of a ~~process~~ <u>remote common gateway interface process that retrieves objects from a data store</u>;

detecting the ~~embedded code~~ information representing the address of the remote gateway interface process;

executing instructions of the ~~process~~ <u>remote common gateway interface process</u>; and,

providing an image to a display responsive to executing the instructions while providing <u>video in response to</u> the streaming media ~~content~~ <u>file</u>.

27. (original) The method of claim 25, wherein the embedded code includes a variable value used while executing the instructions.